

1° Géométrie: suivant plan
Geometry: See drawing

SCOE.01.0009

2° Caractéristiques initiales

Primary Technical Properties: (before test)

Tension et limites: Tension and limits:		90V/20	150V/20	200V/20	230V/15	230V/20
Tension statique: E-M 100V/s		72V-108V	120V-180V	160V-240V	195V-265V	184V-276V
DC Spark over Voltage: E-E		100/200	200/400	300/500	300/500	300/500
Tension dynamique: E-M		≤700V	≤700V	≤800V	≤800V	≤800V
Impulse Spark over Voltage: 1kV/μs						
Résistance isolement: ≤90V ≥90V		≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ
Insulation Resistance: 50V DC 100V DC						
Capacité: E-M 1MHz		≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF
Capacitance: E-E		≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF
Tension d extinction: RC//:150Ω-100nF;RS=330Ω		≥70V	≥80V	≥80V	≥80V	≥80V
Holdover Voltage: U(I)600V DC;1.5A;50cycle;E-M						
Tension de lueur: Glow Voltage:		≤100V	≤100V	≤100V	≤100V	≤100V
Courant de transition lueur/arc: Glow to arc transition current:		0.5A	0.5A	0.5A	0.5A	0.5A
Tension d arc: Arc Voltage:		≤25V	≤25V	≤25V	≤25V	≤25V



3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique: E-M 100V/s		72V-108V	120V-180V	160V-240V	195V-265V	184V-276V
DC Spark over Voltage: E-E		100/200	200/400	300/500	300/500	300/500
Tension dynamique:		≤700V	≤700V	≤800V	≤800V	≤800V
Impulse Spark over Voltage:						
Résistance isolement:		≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ
Insulation Resistance:						
Décharge Alternative 50/60Hz,600V E-M		10A	10A	10A	10A	10A
AC discharge current: 5times,1s interval 3min E1/E2-M		20A	20A	20A	20A	20A
Décharge Impulsionnelle 8/20μs,+5/-5 E-M		10kA	10kA	10kA	10kA	10kA
Impulse discharge current: interval 3min E1/E2-M		20kA	20kA	20kA	20kA	20kA
Décharge Impulsionnelle 8/20μs		25kA	25kA	25kA	25kA	25kA
Impulse discharge current: 1times						
Décharge Impulsionnelle 10/1000μs		100A	100A	100A	100A	100A
Impulse life: 300times,interval 2min						

4° Code:

Part number:

	9290001	9290002	9290005	9290007	9290057
QVGQ2.E184939	YES	YES	YES	YES	YES
					
REG.-Nr.40008209					

1. This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

Date	Code N°
12/11/2007	92 900 XX XX

1° Géométrie: suivant plan

SCOE.01.0009

Geometry: See drawing

2° Caractéristiques initiales

Primary Technical Properties: (before test)

		250V/15	250V/20	260V/20	300V/20	350V/20
Tension et limites:						
Tension and limits:						
Tension statique:	E-M 100V/s	212V-287V	200V-300V	208V-312V	240V-360V	280V-420V
DC Spark over Voltage:	E-E	400/600	400/600	400/600	450/650	500/700
Tension dynamique:	E-M	≤900V	≤900V	≤900V	≤900V	≤900V
Impulse Spark over Voltage:	1kV/μs					
Résistance isolement:	≤90V ≥90V	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ
Insulation Resistance:	50V DC 100V DC					
Capacité:	E-M 1MHz	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF
Capacitance:	E-E	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF
Tension d extinction:	RC//:150Ω-100nF;RS=330Ω	≥80V	≥80V	≥80V	≥80V	≥80V
Holdover Voltage:	U(I)600V DC;1.5A;50cycle;E-M					
Tension de lueur:		≤100V	≤100V	≤100V	≤100V	≤100V
Glow Voltage:						
Courant de transition lueur/arc		0.5A	0.5A	0.5A	0.5A	0.5A
Glow to arc transition current:						
Tension d arc		≤25V	≤25V	≤25V	≤25V	≤25V
Arc Voltage:						



3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique:	E-M 100V/s	212V-287V	200V-300V	208V-312V	240V-360V	280V-420V
DC Spark over Voltage:	E-E	400/600	400/600	400/600	465/650	500/700
Tension dynamique:		≤900V	≤900V	≤900V	≤900V	≤900V
Impulse Spark over Voltage:						
Résistance isolement:		≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ
Insulation Resistance:						
Décharge Alternative	50/60Hz,600V E-M	10A	10A	10A	10A	10A
AC discharge current:	5times,1s interval 3min E1/E2-M	20A	20A	20A	20A	20A
Décharge Impulsionnelle	8/20μs,+5/-5 E-M	10kA	10kA	10kA	10kA	10kA
Impulse discharge current:	interval 3min E1/E2-M	20kA	20kA	20kA	20kA	20kA
Décharge Impulsionnelle	8/20μs	25kA	25kA	25kA	25kA	25kA
Impulse discharge current:	1times					
Décharge Impulsionnelle	10/1000μs	100A	100A	100A	100A	100A
Impulse life:	300times,interval 2min					

4° Code:

Part number:

	9290009	9290059	9290010	9290013	9290015
	YES	YES	YES	YES	YES
QVGQ2.E184939					
					
REG.-Nr.40008209					

1. This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

Date	Code N°
12/11/2007	92 900 XX XX

1° Géométrie: suivant plan
Geometry: See drawing

SCOE.01.0009

2° Caractéristiques initiales

Primary Technical Properties:(before test)

Tension et limites: Tension and limits:		450V/20	500V/20	600V-15+20		
Tension statique: DC Spark over Voltage:	E-M 100V/s E-E	360V-540V 800/1000	400V-600V 800/1100	510V-720V 850/1250		
Tension dynamique: Impulse Spark over Voltage:	E-M 1kV/μs	≤1100V	≤1200V	≤1200V		
Résistance isolement: Insulation Resistance:	≤90V ≥90V 50V DC 100V DC	≥10GΩ	≥10GΩ	≥10GΩ		
Capacité: Capacitance:	E-M 1MHz E-E	≤0.9pF ≤0.5pF	≤0.9pF ≤0.5pF	≤0.9pF ≤0.5pF		
Tension d extinction: Holdover Voltage:	RC//:150Ω-100nF;RS=330Ω U(I)600V DC;1.5A;50cycle;E-M	≥80V	≥80V	≥80V		
Tension de lueur: Glow Voltage:		≤100V	≤100V	≤100V		
Courant de transition lueur/arc Glow to arc transition current:		0.5A	0.5A	0.5A		
Tension d arc Arc Voltage:		≤25V	≤25V	≤25V		



3° Pouvoir d écoulement: (après tests)

Power-flow Properties:(after life test)

Tension statique: DC Spark over Voltage:	E-M 100V/s E-E	360V-540V 800/1000	400V-600V 800/1100	510V-720V 850/1250		
Tension dynamique: Impulse Spark over Voltage:		≤1100V	≤1200V	≤1200V		
Résistance isolement: Insulation Resistance:		≥1000MΩ	≥1000MΩ	≥1000MΩ		
Décharge Alternative AC discharge current:	50/60Hz,600V 5times,1s interval 3min	E-M 10A 20A	10A 20A	10A 20A		
Décharge Impulsionnelle Impulse discharge current:	8/20μs,+5/-5 interval 3min	E-M 10kA 20kA	10kA 20kA	10kA 20kA		
Décharge Impulsionnelle Impulse discharge current:	8/20μs 1times	25kA	25kA	25kA		
Décharge Impulsionnelle Impulse life:	10/1000μs 300times,interval 2min	100A	100A	100A		

4° Code:

Part number:

	9290020	9290022	9290026		
QVGQ2.E184939	YES	YES			
					
REG.-Nr.40008209					

1. This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

Date	Code N°
12/11/2007	92 900 XX XX